



NDW4010PN1



NDW3010PN1



NDW2010PN1

Product Features

- Height Adjustable Upper Basket
- Water Overflow Protection • Silent Operation • Steel body
- LED Indicator and display options

- سلة عليا قابلة للتعديل • حماية من تدفق الماء
- تشغيل صامت • هيكل من الستانلس ستيل
- مؤشر مضيء وخيارات للعرض

Product Range & Specifications

Model	NDW4010PN1	NDW3010PN1	NDW2010PN1
Origin	CHINA	CHINA	CHINA
Finish	SS Finish	SS Finish	SS Finish
Settings	15 place settings	14 place settings	14 place settings
Performance	A+++	A++	A++
Programs	8 (Auto, Intensive, Normal, Eco, Glass, 90Min, Rapid, Soak)	8 (Auto, Intensive, Normal, ECO, Glass, 90Min, Soak)	8 (Auto, Intensive, Normal, ECO, Glass, 90Min, Soak)
Interior	Stainless Steel	Stainless Steel	Stainless Steel
Control	Acoustic end of cycle indicator	Acoustic end of cycle indicator	Acoustic end of cycle indicator
Height Adjustable Upper Basket	Yes	Yes	Yes
Child Lock	Yes	Yes	Yes
Delay Start	24 Hours Delay Start	24 Hours Delay Start	24 Hours Delay Start
Noise level	42 DB	49 DB	49 DB
Function	Extra drying/Power wash/Express/ Energy Saving	Extra drying, power wash	Extra drying, power wash
Voltage/Frequency	220-240V/50/60HZ	220-240V/50/60HZ	220-240V/50/60HZ
Water Overflow Protection	Yes	Yes	Yes
Water consumption	11 L	11 L	11 L
Product Dimension (W X D X H) mm	600 X 600 X 845	600 X 600 X 845	600 X 600 X 845
Packing Dimension (W X D X H) mm	645 X 645 X 884	645 X 645 X 884	645 X 645 X 884
Loading/40'HQ	162 PCS	162 PCS	162 PCS

*Product Range & Specification subject to change without prior notice for product improvement & compliance requirements.



NDW4000SN1



NDW3000SN1



NDW2000SN1

Product Features

- Height Adjustable Upper Basket
- Water Overflow Protection • Silent Operation • Steel body
- LED Indicator and display options

- سلة عليا قابلة للتعديل • حماية من تدفق الماء
- تشغيل صامت • هيكل من الستانلس ستيل
- مؤشر مضيء وخيارات للعرض

Product Range & Specifications

Model	NDW4000SN2	NDW3000SN2	NDW2000SN2
Origin	CHINA	CHINA	CHINA
Colour	SS Finish	SS Finish	SS Finish
Settings	14 place, Touch Model, INOX panel	14 place settings	12 place settings
Performance	A++AA	A++AA	A+AA
6 Programs	6 (Intensive/Eco/Light/pre-Rinse/Rapid/Crystal)	6 (Intensive/Eco/Light/pre-Rinse/Rapid/Crystal)	6 (Intensive/Eco/Light/pre-Rinse/Rapid/Crystal)
Interior	Stainless Steel	Stainless Steel	Stainless Steel
Control	Touch control with LED Indicator	Electronic control with LED Indicator	Electronic control with LED Indicator
Height Adjustable Upper Basket	Yes	Yes	Yes
Child Lock	Yes	Yes	Yes
Delay Start	1-24 Hours Delay Start	1-24 Hours Delay Start	3/6/9 Hours Delay Start
Noise level	49 DB	49 DB	52 DB
Approval	GS/CE/CB/SAA	GS/CE/CB/SAA	GS/CE/CB/SAA
Function	3 in 1	3 in 1	
Voltage/Frequency	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ
Water Overflow Protection	Yes	Yes	Yes
Water consumption	11 L	11 L	14 L
Product Dimension (WXDXH) mm	600 X 600 X 850	600 X 600 X 850	600 X 600 X 850
Packing Dimension (WXDXH) mm	642 X 637 X 888	642 X 637 X 888	642 X 637 X 888
Loading/40'HQ	162 PCS	162 PCS	162 PCS

*Product Range & Specification subject to change without prior notice for product improvement & compliance requirements.



Product Features

- Height Adjustable Upper Basket • Easy to use
- SS Body • Compact Design • Water Overflow Protection
- 7 Programs

- سلة عليا قابلة للتعديل • سهل الاستخدام
- هيكل من الستانلس ستيل • تصميم مضغوط
- حماية من تدفق الماء • ٧ برامج

Product Range & Specifications

Model	NDW1010N1T
Origin	CHINA
Colour	Steel Finish
Settings	6 plate settings/8 plate settings
Performance	A+
Programs	7 (Intensive, Normal, ECO, Glass, 90min, Rapid, Babycare)
Interior	Stainless Steel
Control	LED Control
Height Adjustable Upper Basket	Yes
Delay Start	1-24 Hours Delay Start
Noise level	49 DB
Function	Extra drying, Power wash
Voltage/Frequency	(220-240)V/50HZ
Water Overflow Protection	Yes
Water consumption	11 L
Product Dimension (W X D X H) mm	550 X 500 X 438
Packing Dimension (W X D X H) mm	605 X 555 X 510
Loading/40'HQ	400

*Product Range & Specification subject to change without prior notice for product improvement & compliance requirements.